



卓颖机械（上海）有限公司
JOY MACHINERY (SHANGHAI) CO.,LTD.

服务热线
021-60832839/13621925718

Website: www.shairbuild.com

Email: info@shairbuild.com

卓颖机械（上海）有限公司

地址: 上海市浦东新区川沙路1098号

邮编: 201499

网址: www.sh-joymachinery.com

www.shairbuild.com

邮箱: info@shairbuild.com

电话: 0086 21 60832839

JOY MACHINERY (SHANGHAI) CO.,LTD.

ADD: No.1098, Chuansha Road, Pudong District, Shanghai, China.

Postal code: 201499

Website: www.sh-joymachinery.com

www.shairbuild.com

E-mail: info@shairbuild.com

Tel: 0086 21 60832839



2026 Version

卓颖机械（上海）有限公司
JOY MACHINERY (SHANGHAI) CO.,LTD.

卓颖机械
产品样册

PRODUCTS
CATALOGUE





公司简介 COMPANY PROFILE

卓颖机械（上海）有限公司是一家专注于空气压缩机的专业化企业，致力于为客户提供稳定、节能、高效、智能化的压缩空气解决方案为己任，让全球用户享受卓颖产品带来的不一样的美好体验。

卓颖生产管理严格遵循 ISO9001 国际质量体系，可提供全面的智能空压机产品，包括但不限于：低于、常压、高压螺杆空压机、永磁变频双级压缩空压机、无油空压机、移动空压机、后处理设备。产品广泛应用于机械制造、食品医药、石油化工等领域。公司本着“客户的满意就是我们矢志不渝的追求”的企业理念，产品出口亚洲、欧洲、美洲、非洲等国家和地区，获得良好的市场口碑。

“卓而不凡，颖领科技”——卓颖机械（上海）有限公司欢迎各界惠顾，让我们共同携手，共创美好未来！

JOY MACHINERY (SHANGHAI) CO., LTD. specializes in air compressors, committed to providing customers with stable, energy-saving, efficient and intelligent compressed air solutions, offering global users to enjoy the unique and beautiful experience of JOY MACHINERY products.

JOY MACHINERY strictly follows the ISO9001 international quality system and can provide a comprehensive range of intelligent air compressor products, including but not limited to: low-pressure, normal pressure, high-pressure screw air compressors, permanent magnet variable frequency two-stage compression air compressors, oil-free air compressors, mobile air compressors, and post-treatment equipment. The product is widely used in fields such as mechanical manufacturing, food and medicine, and petrochemicals etc. The company adheres to the corporate philosophy of "customer satisfaction is our unwavering pursuit", our products are exported to countries and regions such as Asia, Europe, America, Africa, etc., gaining a good market reputation.

JOY MACHINERY (SHANGHAI) CO., LTD. welcomes customers from all walks of life to join hands and create a better future together, with the slogan "Extraordinary quality, Leading Technology"!



目录	CONTENTS.....1
公司介绍	COMPANY PROFILE.....2
柴油移动螺杆空压机	Diesel Portable Screw Air Compressor.....3
柴油移动螺杆空压机	Diesel Portable Screw Air Compressor.....3
电动移动螺杆空压机	Electric Portable Screw Air Compressor.....5
电动移动螺杆空压机	Electric Portable Screw Air Compressor.....5
汽油移动螺杆空压机	Petrol Portable Screw Air Compressor.....7
汽油移动螺杆空压机	Petrol Portable Screw Air Compressor.....7
小型电动移动螺杆空压机	Miniature Electric Portable Screw Air Compressor.....9
小型电动移动螺杆空压机	Miniature Electric Diesel Portable Screw Air Compressor9
应用案例	Application case.....10

柴油移动式空压机 (37-410KW)
Diesel Portable Screw Air Compressor (37-410KW)



柴油移动空压机是工程机械设备理想动力源选择,由于不需要电力作为动力源,加之良好的机动性,使其成为道路、矿山、野外等施工的首要选择。

性能优越,低能耗、高性能,能够提供持续、充足的压力和流量,适用于恶劣的工况,拥有重载型底盘,可靠且耐用,易于维护。

大容量油箱,加长运行时间。

加装油水分离器,解决燃油油品问题。

集成数字显示屏,监控,操作简单。

双压系统,高低压一键切换,一机多能。

核心部件—主机



柴油移动空压机专用主机,可靠稳定,效率高。

涵盖单级压缩、双级压缩、低压、中压、高压,满足各种工况要求。

澎湃动力—发动机

配置康明斯、洋马、玉柴等知名发动机品牌

涡轮增压,高压共轨技术,动力强劲,稳定性好

满足国内外客户多样化需求



康明斯



洋马

过滤系统--油滤



国内外知名品牌

确保油滤顺畅

动力之源—电瓶

大容量骆驼蓄电池,

经久耐用。



气控系统



规格参数表 Technical Parameters													
型号 Model	空压机							柴油机					
	排气量 Capacity m³/min	排气压力 Pressure Mpa	压缩级数	行走系统	外形尺寸 长宽高L*W*H mm	接口尺寸 Outlet	净重 Weight KG	制造厂家 Make	额定功率 KW/HP	额定转速 RPM	空载转速 RPM	油箱容量 L	
JMCY-5/8	5	0.8	单级	两轮	1950*1460*1400	G1" 2-G 3/4"	960	洋马	36.8/50	2400	1500	60	
JMCY-7/8	7	0.8	单级	两轮	2100*1460*1400	2-G1" G1 1/2"	1150	玉柴	55/75	2400	1500	60	
JMCY-12/8	12	0.8	单级	两轮	2250*1810*1950	G1" G1 1/2"	2000	康明斯	93/125	2200	1500	120	
JMCY-12/13	12	1.3	单级	两轮	2250*1810*1950	G1" G1 1/2"	2000	康明斯	110/150	2200	1500	120	
JMCY-18/8	18	0.8	单级	两轮 四轮	2750*1680*2280	G1" G2"	2600	康明斯	132/180	2200	1500	180	
JMCY-24/8-II	24	0.8	两级	两轮 四轮	2750*1680*2280	G1" G2"	2700	康明斯	153/205	2200	1500	180	
JMCY-28/8-II	28	0.8	两级	两轮 四轮	3000*1780*2620	G1" G2"	3300	康明斯	191/260	2200	1500	320	
JMCY-18/10	18	10.0	单级	两轮 四轮	2750*1680*2280	G1" G2"	2700	玉柴	141/190	2100	1350	180	
JMCY-16/13	16	1.3	单级	两轮 四轮	2750*1680*2280	G1" G2"	2700	玉柴	141/190	1900	1350	180	
JMCY-18/14-II	18	1.4	两级	两轮 四轮	2750*1680*2280	G1" G2"	2850	玉柴	141/190	2100	1350	180	
JMCY-15/17-II	15	1.7	两级	两轮 四轮	2750*1680*2280	G1" G2"	2850	玉柴	141/190	1900	1350	180	
JMCY-20/14-II	20	1.4	两级	两轮 四轮	2750*1680*2280	G1" G2"	2850	玉柴	141/190	2100	1350	180	
JMCY-18/17-II	18	1.7	两级	两轮 四轮	2750*1680*2280	G1" G2"	2850	玉柴	141/190	1900	1350	180	
JMCY-20/14-II	20	1.4	两级	两轮 四轮	2750*1680*2280	G1" G2"	2950	玉柴	162/220	2000	1350	180	
JMCY-18/18-II	18	1.8	两级	两轮 四轮	2750*1680*2280	G1" G2"	2950	玉柴	162/220	1800	1350	180	
JMCY-22/16-II	22	1.6	两级	两轮 四轮	2750*1680*2280	G1" G2"	2950	玉柴	162/220	2000	1350	180	
JMCY-19/19-II	19	1.9	两级	两轮 四轮	2750*1680*2280	G1" G2"	2950	玉柴	162/220	1800	1350	180	
JMCY-22/18-II	22	1.8	两级	两轮 四轮	3000*1780*2620	G1" G2"	3100	玉柴	191/260	2000	1350	320	
JMCY-21/20-II	21	2.0	两级	两轮 四轮	3000*1780*2620	G1" G2"	3100	玉柴	191/260	1800	1350	320	
JMCY-25/16-II	25	1.6	两级	两轮 四轮	3000*1780*2620	G1" G2"	3200	玉柴	191/260	1930	1350	320	
JMCY-23/20-II	23	2.0	两级	两轮 四轮	3000*1780*2620	G1" G2"	3200	玉柴	191/260	1800	1350	320	
JMCY-27/16-II	27	1.6	两级	两轮 四轮	3000*1780*2620	G1" G2"	3300	玉柴	191/260	2000	1350	320	
JMCY-25/22-II	25	2.2	两级	两轮 四轮	3000*1780*2620	G1" G2"	3300	玉柴	191/260	1900	1350	320	
JMCY-32/20-II	32	2.0	两级	四轮	3000*1780*2620	G1" G2"	3300	康明斯	264/360	2000	1350	400	
JMCY-29/23-II	29	2.3	两级	四轮	3000*1780*2620	G1" G2"	3300	康明斯	264/360	1900	1350	400	
JMCY-36/15-II	36	1.5	两级	四轮	3500*1950*2670	G1" G2"	4500	玉柴	295/400	1880	1350	520	
JMCY-31/25-II	31	2.5	两级	四轮	3500*1950*2670	G1" G2"	4500	玉柴	295/400	1750	1350	520	
JMCY-35/20-II	35	2.0	两级	四轮	3000*1780*2620	G1" G2"	4000	康明斯	316/430	1900	1350	400	
JMCY-31/25-II	31	2.5	两级	四轮	3000*1780*2620	G1" G2"	4000	康明斯	316/430	1750	1350	400	
JMCY-38/25-II	38	2.5	两级	四轮	3700*2100*2770	G1" G2"	6000	康明斯	410/550	1850	1350	700	
JMCY-35/34-II	35	3.4	两级	四轮	3700*2100*2770	G1" G2"	6000	康明斯	410/550	1650	1350	700	
JMCY-38/25-II	38	2.5	两级	四轮	3700*2100*2770	G1" G2"	6000	玉柴	410/550	1850	1350	700	
JMCY-35/34-II	35	3.4	两级	四轮	3700*2100*2770	G1" G2"	6000	玉柴	410/550	1700	1350	700	

电动移动式空压机 (75-315KW)
Electrical Portable Screw Air Compressor (75-315KW)



电动移动空压机适用于有电源或者移动电源的地方。结构紧凑、轻巧、便于移动。电器系统采用防雨、宽电压设计，克服野外电压过低、电压不稳的问题。

集成数字显示屏，监控，操作简单。

管路采用耐高温管、耐高压管，寿命长，外观美观。

核心部件—主机



电动空压机专用主机，可靠稳定，效率高。

涵盖单级压缩、双级压缩、低压、中压、高压，满足各种工况要求。

两级压缩型采用大机头，转速低，效率高。



澎湃动力—电动机

标配 YE3 高效电机，启动扭矩大，启动电流小。

两级压缩选用四极电机，转速低，低电压启动性能强。

防护等级 IP55，F 级绝缘，适合 24 小时连续工作。

精选零部件—优质、稳定



空滤

重载型两级旋风空气过滤器，超细过滤精度，可延长空压机寿命。



显示屏

友好的人机交互界面，让您能够掌控自己的供气系统



启动

宽电压启动，解决电压不稳的问题



油气分离器

使用高温管路连接，精细分离效果保证更高质量的压缩空气

规格参数表 Technical Parameters							
型号 Model	功率 Power	排气量 Capacity m³/min	排气压力 Pressure Mpa	压缩 级数	外形尺寸 长宽高L*W*H mm	接口尺寸 Outlet	净重 Weight KG
JMDY-13/8	75	13	0.8	单级	2550*1400*1910	G1" G2"	1500
JMCY-10/13	75	10	1.3	单级	2550*1400*1910	G1" G2"	1500
JMCY-16/8	90	16	0.8	单级	2550*1400*1910	G1" G1 1/2"	1600
JMCY-13/14	90	13	1.4	单级	2550*1400*1910	G1" G1 1/2"	1600
JMCY-20/8	110	20	0.8	单级	3100*1685*2220	G1" G2"	2300
JMCY-16/12	110	16	1.2	单级	2550*1400*1910	G1" G2"	2300
JMCY-12/18	110	12	1.8	单级	3100*1685*2220	G1" G2"	2300
JMCY-24/8	132	24	0.8	单级	3100*1685*2220	G1" G2"	2500
JMCY-16/14	132	16	1.4	单级	3100*1685*2220	G1" G2"	2500
JMCY-15/18	132	15	1.8	单级	3100*1685*2220	G1" G2"	2500
JMCY-16/14-II	90	16	1.4	两级	3100*1685*2220	G1" G2"	2500
JMCY-16/8-II	110	16	0.8	两级	3100*1685*2220	G1" G2"	2800
JMCY-18/20-II	110	18	2.0	两级	3100*1685*2220	G1" G2"	2800
JMCY-21/18-II	132	21	1.8	两级	3000*1680*2160	G1" G2"	2800
JMCY-23/20-II	132	23	2.0	两级	3000*1680*2160	G1" G2"	3300
JMCY-23/18-II	160	23	1.8	两级	3000*1680*2160	G1" G2"	3600
JMCY-25/20-II	160	25	2.0	两级	3000*1680*2160	G1" G2"	3600
JMCY-24/20-II	185	24	2.0	两级	3000*1680*2160	G1" G2"	3700
JMCY-26/22-II	185	26	2.2	两级	3000*1680*2160	G1" G2"	3700
JMCY-24/25-II	185	24	2.5	两级	3000*1680*2160	G1" G2"	3700
JMCY-26/20-II	200	26	2.0	两级	3000*1680*2160	G1" G2"	3700
JMCY-28/23-II	220	28	2.3	两级	3500*1950*2600	G1" G2"	5000
JMCY-31/25-II	280	31	2.5	两级	3500*1950*2600	G1" G2"	5500
JMCY-30/7-II	132	30	0.7	两级	3000*1680*2160	DN80	3400
JMCY-36/7-II	160	36	0.7	两级	3050*1820*2660	DN80	4200
JMCY-42/7-II	185	42	0.7	两级	3050*1820*2660	DN80	4200
JMCY-46/7-II	200	46	0.7	两级	3500*1950*2600	DN125	5000
JMCY-51/7-II	220	51	0.7	两级	3500*1950*2600	DN125	5500
JMCY-57/7-II	250	57	0.7	两级	3700*2100*2720	DN125	7500
JMCY-62/7-II	280	62	0.7	两级	3700*2100*2720	DN125	7500
JMCY-70/7-II	315	70	0.7	两级	3750*2250*2850	DN150	8500

汽油移动螺杆机 (2.2-7.5KW)
Petrol Portable Screw Air Compressor (2.2-7.5KW)



后处理 Air treatment

汽油机 Petrol portable compressor



发动机 Engine
本田 Honda, 隆鑫 Longxin



主机 Air end
高性能主机



冷却器 Cooler
订制加大型冷却器，确保机器正常运行



空滤 Air filter
从进入压缩机的空气中去除杂质和颗粒物



油分芯 Oil/air separator
外置油分芯，更换便捷



运输 Transportation
紧凑型设计，方便运输



- | | |
|-----------|-----------|
| 1 、 排气口 | 7、油分芯 |
| 2 、 冷却器 | 8、空滤（空压机） |
| 3 、 油滤 | 9、空滤（发动机） |
| 4 、 电池 | 10、发动机油滤 |
| 5 、 主电源开关 | 11、油尺 |
| 6 、 汽油过滤器 | |

规格参数表 Technical Parameters						
型号 Model	功率 Power KW/HP	排气量 Capacity m³/min	排气压力 Pressure Mpa	发动机 Petrol engine	外形尺寸 长宽高L*W*H mm	净重 Weight KG
JMQY-1.5/5	11/15	1.5	0.5	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1000*750*700	175
JMQY-1.35/7	11/15	1.35	0.7	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1000*750*700	175
JMQY-2.0/7	16.5/22	2.0	0.7	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1250*860*810	245
JMQY-1.7/8	16.5/22	1.7	0.8	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1250*860*810	245
JMQY-1.5/10	16.5/22	1.5	1.0	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1250*860*810	245
JMQY-1.2/13	16.5/22	1.2	1.3	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1250*860*810	245
JMQY-1.0/15	16.5/22	1.0	1.5	本田 HONDA/力帆 Lifan /隆鑫 LONGXIN	1250*860*810	245



小型电动移动螺杆机 (2.2-7.5KW)

Miniature Electrical Portable Screw Air Compressor (2.2-7.5KW)



产品特点 Product Feature

电机功率 Motor Power :2.2-7.5 KW

排气量 Discharge delivery: 0.30-1.0 m3/min

排气压力 Discharge Pressure: 0.8-1.25 Mpa

电源有单相、三相，满足客户的各种需求

The power supply is available in single-phase and three-phase configurations to meet various customer needs

采用优质主机、电机，运行稳定，故障率低

Using high-quality air end and motor, stable operation, low failure rate

自带储气罐，机身带轮子，移动使用方便，可替代活塞机
Equipped with a built-in air tank and wheels on the body, it is easy to move and use, and can replace piston engines

规格参数表 Technical Parameters								
型号 Model	功率 Power (KW/Hp)	电压 Voltage (V/Hz)	排气量 Capacity (m³/min)	排气压力 Pressure (Mpa)	储气罐容积 Tank volume (L)	噪音 Noise level (Db)	冷却方式 Cooled way	外形尺寸 Dimension L*W*H(mm)
JMDY-4/10D	2.2/4	220/50	0.3	0.8-1.0	90	78±2	风冷 Air cooled	940*365*940
JMDY-4/10S	2.2/4	380/50	0.3	0.8-1.0	90	78±2	风冷 Air cooled	940*365*940
JMDY-5.5/10D	4.5/6	220/50	0.55	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-5.5/10S	4.5/6	380/50	0.55	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-7.5/10S	5.5/7.5	380/50	0.7	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-10/10S	7.5/10	380/50	1.0	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-10/12.5S	7.5/10	380/50	0.8	1.1-1.25	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-10YPM/10S	7.5/10	380/50	1.0	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-10YPM/10D	7.5/10	220/50	1.0	0.8-1.0	120	78±2	风冷 Air cooled	1060*420*1020
JMDY-10YPM/12.5D	7.5/10	220/50	0.8	1.1-1.25	120	78±2	风冷 Air cooled	1060*420*1020

应用案例

Application cases

